

NBS Specification

L20 DOORS / SHUTTERS / HATCHES

480 DOORSETS: STAINLESS STEEL

Supplier: GSL Doors, 11 Goodwood Close, Lichfield, Staffs, WS14 9XZ
Telephone 01543 304781 Fax 01543 410660
Website: www.gsldoors.co.uk Email: info@gsldoors.co.uk

Product Reference: GSLSS

Door Leaf:

Core: Internally stiffened, insulated and sound deadened with pre-expanded, small cell honeycomb core material and laminated under pressure to the face skins.

Skin: 2 skins of 1.2 mm (18 ga) thick, 304 grade stainless steel, 44mm thick door with no face seams. Face skins are connected by a "deep pocket" interlocking edge lock seam for added strength and durability.

Finish as delivered: Brushed effect to stainless steel.

Frame and architraves:

1.5 mm (16 ga) thick stainless steel forming a double/single rebate profile. Fully protected header allows for a smooth butt-joint with the vertical frame posts.

Finish as delivered: Brushed effect to stainless steel.

Glazing details: Where applicable provide doors with vision panels meeting the requirements of the performance specification.

Ironmongery:

Hinges - 1.5 pairs per leaf of 102 x 76mm template drilled stainless steel hinges.

Door to be prepared to accommodate client specified hardware.

Fixing:

Frames are provided with three fixings per jamb with built in adjustment and completed by matching colour co-ordinated cover caps.